


DIO GRADEVINE KOJI SE REKONSTRUIRA

DIO GRADEVINE KOJI SE ZADRŽAVA

TLOCRT SUTERENA

ново stanje



ISKAZ NETTO POVRŠINA – dio koji se rekonstruira:

1. hodnik	1. P=14,17 m2
2. spremište	2. P=60,41 m2
3. spremište	3. P=38,74 m2
4. kotlovnica	4. P=23,29 m2
ZATVORENI PROSTORI – neto	
P=136,61 m2	
SVEUKUPNO – neto	
P=136,61 m2	

- TUMAČ ZNAKOVA

 rasvjetno tijelo

 zidna armatura

 rasvjetno tijelo sa senzorskim paljenjem

 noćno (požarno) svjetlo - led

 panik rasvjeta

 termostat

 JPR tipkalo

 izmjenični interfonski aparat sa el. bravom

 el. zvono

 oznaka strujnog kruga

 telefonska priključnica

 antenska priključnica

 prekidač obični


 prekidač izmjenični

 prekidač izmjenični dvostruki

 prekidač serijski

 prekidač križni

 taster (el. zvona ili stubišnog automata)

 prekidač kupaoński (indikator)

 fluo svjetiljka

 razvodni omar

 šuko priključnica

 električni grijač vode (EGV)

 kutija za izjednačenje potencijala (KIP)